



PDU24006 | METERED ATS PDU SERIES



Deliver and monitor reliable, redundant power to electronic equipment, servers, and network/telecom devices

Ensure continued operation of critical devices with the CyberPower PDU24006 Metered ATS PDU. Ideal for data centers and network closets, this unit provides power redundancy to single-corded connected equipment. If power for the primary source exceeds the lower or upper thresholds, or if power fails, the PDU will switch to the secondary power source to ensure continuous operation. The PDU will switch back to the primary power source when incoming power becomes stable.

The PDU24006 supports inputs between 200-240V and includes (8) IEC C13 and (2) IEC C19 outlets. Dual NEMA L6-20P power cords are plugged into separate power sources (A and B), and information about each power source is provided via LED indicator lights on the front of the unit. Other features include an LCD with selectable background color, upgradeable firmware, and network-grade plugs and outlets. The CyberPower PDU24006 is protected by a three-year limited warranty.

TYPICAL APPLICATIONS

- Telecom Installations
- Network Closets
- Data Centers

FEATURES

- Phase: Single
- Amps: 20A (Derated to 16A)
- Volts: 200-240V
- Frequency: 50/60Hz
- Plug type: 2 x NEMA L6-20P
- Outlets: 8 x IEC-320 C13, 2 x IEC-320 C19
- Size: 1U Rackmount
- Warranty: Three-Year



Corporate Armor

sales@corporatearmor.com

877.449.0458

SPECIFICATIONS

INPUT	
Cord Length	10 ft (3.0 m)
Derated Input Current	16 A
Input Frequency Range	50 Hz - 60 Hz
Input Plug Type	2 x NEMA L6-20P
Maximum Input Current	20 A
Nominal Input Voltage	240 - 200 VAC
Phase	Single Phase
Plug Style	Straight

OUTPUT	
Nominal Output Voltage	240 - 200 VAC
Outlet Banks	1
Outlet Type	8 - IEC-320 C13 2 - IEC-320 C19
Outlets - Total	10
Overload Protection	None
Power Source Transfer Time	2-7 ms
Source Failure Detection Time	2-3 ms
Total Transfer Time	<10 ms

PDU24006

METERED ATS PDU SERIES



SPECIFICATIONS CONT.

MANAGEMENT & COMMUNICATIONS		PHYSICAL DIMENSIONS	
Hardware Connection Port	Serial (RJ45)	Physical Dimensions - WxHxD (cm)	43.31 x 4.45 x 21.46 cm
LCD	Multifunction LCD	Physical Dimensions - WxHxD (mm)	433 x 44 x 215 mm
LED Indicators	Source Status Source Selected Output Normal / Warning / Critical Status	Physical Dimensions - WxHxD (in.)	17.05 x 1.75 x 8.45 in.
Upgradeable Firmware	Yes	Weight (kg)	4.99 kg
PHYSICAL		Weight (lb)	11.0 lbs.
Color	Black	SHIPPING DIMENSIONS	
Cord Retention Tray/ Cord Organizers	Yes	Shipping Dimensions - WxHxD (cm)	54.99 x 12.45 x 39.8 cm
External Site Ground Pin	Yes	Shipping Dimensions - WxHxD (mm)	549.91 x 124.46 x 398.02 mm
Form Factors Supported	1U Rackmount	Shipping Dimensions - WxHxD (in.)	21.65 x 4.9 x 15.67 in.
Material of Construction	Metal	Shipping Weight (kg)	6.35 kg
Rack Height	1U	Shipping Weight (lbs.)	14.0 lbs.
Style	Rackmount	ENVIRONMENTAL	
		Operating Elevation	0 - 13,123 ft (0 - 4,000 m)
		Operating Relative Humidity	0 - 95 % (non-condensing)
		Operating Temperature	32 - 113 °F (0 - 45 °C)
		Storage Elevation	0 - 49,213 ft (0 - 14,999 m)
		Storage Temperature	5 - 131 °F (-15 - 55 °C)
		CERTIFICATIONS	
		Environmental	RoHS Compliant
		Safety	UL62368 FCC Class A cTUVus
		WARRANTY	
		Extended Warranty Option	WEXT5YR-PDU1B
		Product Warranty	Three-Year Limited